



LOCQUET
POWER & LIGHT



Specifications

Max. power 400V	22 kVA
Continuous power	20 kVA
Emissions standard	Stage IIIA / V
Speed/frequency	1500 rpm / 50 Hz
Type of motor	Perkins*
Alternator	Stamford*
Cooling	water
Fuel	diesel
Internal tank capacity	1.200 L
Avg. fuel cons. 50%	1,5 to 2 L/h
Service interval	500 h
Sound level	51 dBA@7m
Dimensions (WxLxH)	220 x 110 x 180 cm
Weight	2.200 kg
OUT	2x 16A Schuko 230V 2x 32A CEE 400V

*The model may vary depending on the specific generator.

GENERATORS

20 kVA Greenline generator

Code: 20 KVA SUPERSOUND

20 kVA Greenline

Super silent 20 kVA power generator with an internal fuel tank capacity of **1.200L**.

- ▶ Available on request in compliance with **Stage V** emission standards
- ▶ **Deep Sea 7310** Autostart panel
- ▶ Adjustable timer
- ▶ 300 mA residual current device, adjustable
- ▶ Connection for external fuel tank
- ▶ Battery charger and battery switch
- ▶ Suitable for use with a Battery Pack
- ▶ Remote monitoring (optional)
- ▶ Suitable for **power management** and twin-set synchronous configuration



The 20 kVA Greenline generator is also available on a trailer.



©2026-2027 | Locquet Power & Light BV | All rights reserved | The images shown may differ from the actual product.
Specifications are subject to change without prior notice.

www.locquet.com

LOCQUET POWER & LIGHT BV ● Karreweg 139A, 9770 Kruisem ● T 0032 (0)9 388 80 85 ● power@locquet.com